

2D-3D PROJECTOR

D512-3D



Taking 3D Projection to a New Level

The Vivitek D512-3D digital projector plays 3D content from virtually any video source, and can convert 2D content to 3D without an external box.

Features

- DLP® and BrilliantColor™ technologies for sharp and detailed image quality
- Integrated 2D to 3D content conversion technology
 - Can automatically converts any 2D content into 3D ready material through HDMI port by pressure of a single button for enhanced viewing pleasure
- High-efficiency lamps that last up to 4000 hours (in economy mode)
- High brightness and contrast ratio
- Built-in enhanced color and display adjustments
- Connectivity options including: HDMI V1.3, and RS-232C
- Keypad lock prevents accidental system adjustments
- Great portability at 1.9kg

Prod	uct	Pho	otos
	uct		,,,,









Specifications		
Brightness	2600 ANSI Lumens	
Native Resolution	SVGA (800 x 600)	
Maximum Resolution	UXGA (1600 x 1200) @60Hz	
Contrast Ratio	3000:1	
Lamp Life and Type	3000 / 4000 Hours (Std. / Eco. Mode), 180W	
Display Type	Single 0.55" DLP® Technology by Texas Instruments	
Throw Ratio	1.92 - 2.14:1	
Image Size (Diagonal)	40" - 300"	
Projection Distance	1 - 10m	
Projection Lens	F = 2.52 - 2.73, f = 24.34 - 25.95mm	
Zoom Ratio	1.1x	
Aspect Ratio	4:3 Native, 16:9 Compatible	
Offset	128%	
Keystone Correction	Vertical ± 15°	
Horizontal Frequency	15, 30 - 90kHz	
Vertical Scan Rate	43 - 85Hz	
Speakers	2 Watt	
Lens Shift Range	N/A	
Video Compatibility	SDTV(480i, 576i), EDTV (480p), HDTV (720p, 1080i/p),	
	NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM	
I/O Connection Ports	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p,	
	1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I,	
	M, N), SECAM (B, D, G, K, K1, L)	
Projection Method	Table Top, Ceiling Mount (Front or Rear)	
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock	
Dimensions (W x D x H)	261 x 190 x 78mm	
Weight	1.9kg	
Noise Level	31dB/28dB (Normal / Eco Mode)	
Power	Supply: AC 100-240V, 50/60Hz	
	Consumption: 205W (Eco. Mode), 230W (Std. Mode),	
	<1W (Standby)	
Warranty	2-Year warranty on projector, 1-Year or 1,000h on	
	lamp	
Standard Accessories	AC Power Cord, VGA Cable, Carrying Case, Remote	
	Control, Batteries for Remote, Lens Cap,	
	Documentation Kit	
Optional Accessories	Replacement Lamp, Remote, Carrying Case	









