

2D-3D PROJECTOR

## D536-3D



## A Whole New Dimension in Projection

The Vivitek D536-3D digital projector takes 2D content and converts it into 3D, as well as displays 3D content from just about any video source without an external box.

## **Features**

- DLP® and BrilliantColor™ technologies for sharp and detailed image quality
- Integrated 2D to 3D content conversion technology
  - Can automatically converts any 2D content into 3D ready material through HDMI port by pressure of a single button for enhanced viewing pleasure
- High-efficiency lamps that last up to 4000 hours (in economy mode)
- High brightness and contrast ratio
- Built-in enhanced color and display adjustments
- 3D ready for gaming and movies
- Connectivity options including: HDMI V1.3, and RS-232C
- Keypad lock prevents accidental system adjustments
- Great portability at 1.9kg

## **Product Photos**









Specifications	
Brightness	3200 ANSI Lumens
Native Resolution	XGA (1024 x 768)
Maximum Resolution	UXGA (1600 x 1200) @60Hz
Contrast Ratio	3000:1
Lamp Life and Type	3000/4000 Hours (Std./Eco. Mode), 240W
Display Type	Single 0.55" DLP® Technology by Texas Instruments
Throw Ratio	1.92 - 2.14:1
Image Size (Diagonal)	40" - 300"
Projection Distance	1 - 10m
Projection Lens	F = 2.52 - 2.73, f = 24.34 - 25.95mm
Zoom Ratio	1.1x
Aspect Ratio	4:3 Native, 16:9 Compatible
Offset	128%
Keystone Correction	Vertical ± 15°
Horizontal Frequency	15, 30-90KHz
Vertical Scan Rate	43 - 85Hz
Speakers	2 Watt
Lens Shift Range	N/A
Video Compatibility	SDTV(480i, 576i), EDTV (480p, 576p), HDTV (720p,
	1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H,
	I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	HDMI v.1.3, VGA-In, S-Video, Composite Video,
	Audio-In RCA (L/R), Audio-In (Mini-Jack), RS-232C
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Security Bar, Keypad Lock
Dimensions (W x D x W)	261 x 190 x 78mm
Weight	1.9kg
Noise Level	35dB/29dB (Normal / Eco Mode)
Power Consumption	Supply: AC 100-240V, 50/60Hz
	Consumption: 230W (Eco. Mode), 300W (Std.
	Mode), <1W (Standby)
Standard Accessories	AC Power Cord, VGA Cable, Carrying Case, Remote
	Control, Batteries for Remote, Lens Cap,
	Documentation Kit
Optional Accessories	Replacement Lamp, Remote, Carrying Case









