

# Vivitek D557W

Widescreen 3D ready projector



## Product Features

- DLP® technology with BrilliantColor™ for vibrant and rich picture quality
- 3,000 ANSI lumens of brightness and 15,000:1 contrast ratio for clear, crisp and bright presentations
- WXGA(1280 x 800) native resolution scalable up to a maximum UXGA (1600 x 1200) resolution
- Innovative 5 segment colorwheel provides improved color reproduction and automatic gain control
- Convenient top loading design for easy lamp replacement
- Multiple inputs for easy connection to a variety of devices: HDMI v1.4, VGA-In (x2), S-Video, composite video
- Source filtering function to save time locating device signal source
- 3D ready with DLP Link and Blu-Ray 3D functionality
- Audio ready with built-in 2 watt audio speaker, audio-in and audio out ports
- Reduces energy consumption to less than 0.5W in stand-by mode
- Keypad lock prevents accidental system adjustments
- 2.3kg/5lbs for easy portability

## Product Photos



Product Specifications	
Display Type	DLP® BrilliantColor™ Technology
Brightness	3000 ANSI Lumens
Native Resolution	WXGA (1280 x 800)
Maximum Resolution	UXGA (1600 x 1200)@60Hz
Contrast Ratio	15,000:1
Uniformity	95%
Lamp Type	190W/160W (Normal/Eco Mode)
Lamp Life	5,000/6,000 Hours (Normal/Eco Mode)
Throw Ratio	1.54 - 1.71:1
Image Size (Diagonal)	27" - 300" (68.6 - 762cm)
Projection Distance	1 - 10m (3.28ft to 32.8ft)
Projection Lens	F = 2.52 - 2.73, f = 21.8 - 24mm
Zoom Ratio	1.1x
Aspect Ratio	16:10 Native
Offset	128% +/-10%
Keystone Correction	Vertical +/-40%, +/-40 Step
Horizontal Frequency	2D: 15, 30 – 91.4kHz/3D: 101.6KHz
Vertical Scan Rate	24 - 30Hz, 47 - 120Hz
Speakers	2W (Mono)
3D Ready	Yes (Supports DLP Link, Blu-Ray 3D)
Video Compatibility	SDTV (480i, 576i), EDTV (480p, 576p), HDTV (720p, 1080i/p), NTSC (M, 3.58/4.43 MHz), PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L)
I/O Connection Ports	HDMI v1.4, VGA-In (x2), S-Video, Composite Video, Audio-In (L/R), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS-232, Mini-USB (Service)
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Keypad Lock
Dimensions (W x D x H)	274.6 x 212 x 100mm (10.8" x 8.3" x 3.9")
Weight	2.3kg (5lbs)
Noise Level	35dB/32dB (Normal/Eco Mode)
Power Supply	AC 100-240V, 50/60Hz
Power Consumption	200W (Eco. Mode), 240W (Normal Mode), <0.5W (Standby)
Standard Accessories	AC Power Cord, VGA Cable, Remote Control w/Batteries, Documentation Kit
Optional Accessories	Replacement Lamp, Remote w/Laser Pointer

©2013 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.

