

Portable Projector

Vivitek DW282-ST

Versatile and value-oriented WXGA short-throw projector with long-life lamp, 3D functionality and built-in audio



Features

- Up to 3,200 ANSI lumens with a 15,000:1 contrast ratio
- Native WXGA resolution with a maximum WUXGA resolution
- Delivers up to a 120" image from a distance close to the projection surface
- Short throw projection allows presenter to stand in front of the screen without blocking image, casting shadows and eye glare
- DLP® and BrilliantColor™ technologies for distinct and vibrant images
- Low cost of ownership and maintenance with an energy efficient lamp for up to 10,000 hours (Dynamic Eco. Mode) of usage
- 6 segment (RGBYCW) color wheel for improved and vivid color reproduction
- Manual zoom and focus for easy adjustment and positioning flexibility
- 2W of total stereo audio power with multiple audio-in and audio-out ports
- Top sided lamp cover for simple lamp removal and insertion
- Intuitive multiple language OSD (On-screen Display) menu
- Environmentally friendly with less than 0.5W of power in stand-by mode
- Portable and lightweight at only 2.6kg (5.7lbs)
- Anti-theft security features include: Kensington® security slot, and security bar

Specifications

Display Type	Single Chip 0.65" DLP Technology by TI
Brightness	3,200 ANSI Lumens
Native Resolution	WXGA (1,280 x 800)
Maximum Resolution	WUXGA (1,920 x 1,200)
Contrast Ratio	15,000:1
Lamp Life/Type	5,000/7,000/10,000 Hours (Normal/Eco./Dynamic Eco), 210W
Throw Ratio	0.48
Image Size (Diagonal)	70" - 120"
Projection Distance	0.74m – 1.26m (2.3' – 4.1')
Projection Lens	F=2.7, f=7.2mm
Zoom Ratio	Fixed Lens
Aspect Ratio	16:10
Offset	101.5%±5%
Keystone Correction	Vertical:±40°
Horizontal Frequency	15 -102kHz
Vertical Frequency	23 - 120Hz
3D Compatibility	Yes
Speaker	2W
Computer Compatibility	VGA (640 x 480) to WUXGA_RB(1920 x 1200)
Video Compatibility	NTSC, PAL, SECAM / 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
I/O Connection Ports	HDMI v1.4b (x2), Composite Video, S-Video, VGA-In (x2), Audio-In (Mini-Jack), VGA-Out, Audio-Out (Mini-Jack), RS232, USB (Service)
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Kensington® Security Slot, Keypad Lock
Dimensions (WxDxH)	332 x 243.6 x 107mm (13" x 9.6" x 4.21")
Weight	2.6kg (5.7lbs)
Available Colors	White
Noise Level	31dB/28dB (Normal/Eco. Mode)
Power Supply	AC 100-240V, 50/60Hz
Power Consumption	240W (Normal Mode), 203W (Eco. Mode), <0.5W (Standby Mode)
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Documentation Kit
Optional Accessories	Lamp

©2017 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subject to change without prior notice.



Photos

